



Declaration of Performance nr.tapco
TPP - TSS - TBB
Plastic anchor for fixing of profiles of ETICS



via Trieste, 1 San Giovanni al Natisone
(UD) Italy - ph. +39 0432 747911
www.friulsider.com - info@friulsider.com

Intended use or uses of the construction product according to ETAG 014

Generic type	Plastic anchor for multiple fixing for anchorage of profiles for bonded thermal insulation composite systems with rendering (ETICS)
Base material (use category)	> A: normal weight concrete acc. to EN 206-1:2003
Material	Sleeve: Polyamide Pa 6 acc. to ISO 1874 Screw: Zinc coated steel 5µm acc. to EN ISO 4042 cl. 5.8 acc. to EN ISO 898-1 Stainless Steel A2-50 AISI304 acc. to EN ISO 3506-1
Durability	> <u>Zinc coated steel</u> for dry internal conditions > <u>Stainless Steel A2 - AISI304</u> for other environmental conditions
Loading	only be used for transmission of wind suction loads and shall not be used for the transmission of dead loads of the ETICS
Fire Resistance	NPD
Fire Reaction	NPD
ETA-10/0190 issued by	ZAG approval body nr.1404
On the basis of	ETAG020
Certificate of Conformity 1404-CPD-1622 issued by	ZAG notified body nr.1404
Under System	2+

Declared performances and design method according to ETAG 014

Essential Characteristics		Performance	
Installation parameters		Ø6	Ø8
d ₀	Nominal diameter of drill bit [mm]	6	8
h _{nom}	Minimum installation depth [mm]	30	40
h _{min}	Minimum thickness of the concrete member C16/20 [mm]	100	100
h ₁	Depth of drill hole to deepest point [mm]	40	50
s _{min}	Minimum spacing C16/20 [mm]	100	100
c _{min}	Minimum edge distance C16/20 [mm]	100	100
Pull-out failure for use in Concrete			
N _{Rk}	Tension characteristic load in C16/20 to C50/60 24°C ²⁾ / 40°C ³⁾ [kN]	1,2	
γ _M ¹⁾	Partial safety factor [-]	2,0	

¹⁾ In absence of other national regulations, see ETAG 014 point 7.1; ²⁾ Maximum long term temperature; ³⁾ Maximum short term temperature.

We inform you that Friulsider is classified in the EC 1907/2006 Reach Directive as a Downstream -user of substances.

The products applied does not contain substances classified as SVHC according to the Candidate List in a concentration equal or greater than 0.1% (weight / weight). Article 31 is not applicable to the present product.

The below performances apply for the following article numbers: **TSS Countersunk head + nail screw**

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. TSS with screw Zinc plated steel	Cod. TSS with screw Stainless steel A2	Cod. TSS with screw threaded part M6 Zinc plated steel	Cod. TSS with screw threaded part M7 Zinc plated steel
Ø6	40	10	FM - TSS Ø6x40	62200b06040	62203x06040	62202b06040	62204b06040
	50	20	FM -TSS Ø6x50	62200b06050	62203x06050	62202b06050	62204b06050
	60	30	FM -TSS Ø6x60	62200b06060	62203x06060		
	80	50	FM -TSS Ø6x80	62200b06080	62203x06080		
Ø8	60	20	FM -TSS Ø8x60	62200b08060			
	80	40	FM -TSS Ø8x80	62200b08080			
	100	60	FM -TSS Ø8x100	62200b08100			
	120	80	FM -TSS Ø8x120	62200b08120			
	140	100	FM -TSS Ø8x140	62200b08140			

⁴⁾ Diameter of anchor sleeve; ⁵⁾ Length of anchor; ⁶⁾ Thickness fixture max.

The below performances apply for the following article numbers: **TPP** Cylindrical head + nail screw

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. TPP with screw Zinc plated steel	Cod. TPP with screw Stainless steel A2
Ø6	40	10	FM-TPP Ø6x40	62700b06040	62701x06040
	50	20	FM-TPP Ø6x50	62700b06050	62701x06050
	60	30	FM-TPP Ø6x60	62700b06060	62701x06060
	80	50	FM-TPP Ø6x80	62700b06080	
Ø8	60	20	FM-TPP Ø8x60	62700b08060	62701x08060
	80	40	FM-TPP Ø8x80	62700b08080	
	100	60	FM-TPP Ø8x100	62700b08100	
	120	80	FM-TPP Ø8x120	62700b08120	
	140	100	FM-TPP Ø8x140	62700b08140	

⁴⁾ Diameter of anchor sleeve; ⁵⁾ Length of anchor; ⁶⁾ Thickness fixture max.

The below performances apply for the following article numbers: **TBB** Large rim + nails crew

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. TBB with screw Zinc plated steel	Cod. TBB with screw Stainless steel A2
Ø6	40	10	FM-TBB Ø6x40	62100b06040	62102x06040
	50	20	FM-TBB Ø6x50	62100b06050	62102x06050
	60	30	FM-TBB Ø6x60	62100b06060	62102x06060
Ø8	80	40	FM-TBB Ø8x80	62100b08080	
	100	60	FM-TBB Ø8x100	62100b08100	
	120	80	FM-TBB Ø8x120	62100b08120	
	140	100	FM-TBB Ø8x140	62100b08140	
	160	120	FM-TBB Ø8x160	62100b08140	

⁴⁾ Diameter of anchor sleeve; ⁵⁾ Length of anchor; ⁶⁾ Thickness fixture max.

The performances of the product identified by the above identification code are in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of Friulsider SpA.

Signed for and behalf of the manufacturer by:

Name and functions	Place and date of issue	Signature
Eng. Vittorio Pilla General Director	San Giovanni al Natisone, 01-07-2013	